

Kap 80 Surface Round Optic Spot Dali/Push Version

03.6021.B1.DA - White/Gold



Designed by Flos Architectural

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Dali/Push dimming 220/240V.




Main specifications

Mounting	Ceiling surface	Dimmable	Yes
Environment	Indoor dry location	Autoprotected Lamp	No
LED type	LED array	Number of heads	1
Lamp category	LED	Source Power (W)	9.2W
Ilcos	No	Source Flux (lm)	908
System Flux (lm)	684		

Optical

Lighting Type	Direct
Lighting distribution	Symmetric
CCT (K)	2700K
CRI>	90
Cold Beam Lighting	No
Beam angle C0-180 (°)	19
Beam angle C90-270 (°)	19



Beam Angle:	19°		
h(m)	E(lx)	D(m)	
1	2879	0.33	
2	720	0.67	
3	320	1.00	
4	180	1.33	
5	115	1.66	

Luminous flux luminaire
684 lm (EXTREME CUT OFF)

Electrical

Insulation class	I	Dimmable type	Dimmable
Frequency (Hz)	50/60		Push,
Main Voltage (Vac)	18.20		Dimmable DALI
Driver	Integrated		1
Dimmable	Yes	Emergency Type	No

Physical

Colour	White/Gold	IP	20
Trim	No	IP external	20
Orientations	Fixed		
Net weight (Kg)	0.45		
Gross weight (Kg)	0.91		

